First Hit

Previous Doc

Next Doc

Go to Doc#

Generate Collection

Print.

L5: Entry 3 of 5

File: JPAB

May 9, 2002

PUB-NO: JP02002129285A

DOCUMENT-IDENTIFIER: JP 2002129285 A

TITLE: STEEL SHEET WITH STRAIN INDUCED TRANSFORMATION TYPE COMPOSITE STRUCTURE

HAVING EXCELLENT BURRING WORKABILITY AND ITS PRODUCTION METHOD

PUBN-DATE: May 9, 2002

INVENTOR-INFORMATION:

NAME

COUNTRY

YOKOI, TATSUO TAKAHASHI, MANABU OKADA, HIROYUKI

INT-CL (IPC): C22C 38/00; C21D 8/02; C21D 9/46; C22C 38/06; C22C 38/58

## **ABSTRACT:**

PROBLEM TO BE SOLVED: To provide a hot rolled steel sheet excellent in fatigue characteristics and burring workability (hole expandability) and having tensile strength of  $\geqslant$ 540 MPa and to provide a production method for inexpensively and stably producing the same steel sheet.

SOLUTION: This  $\underline{\text{steel}}$  sheet with a strain induced transformation type composite structure excellent in burring workability is composed of steel containing 0.01 to 0.3% C, 0.01 to 2% Si, 0.05 to 3% Mn,  $\leq$ 0.1% P,  $\leq$ 0.01% S and 0.005 to 1% Al, and whose microstructure is composed of the composite one containing retained austenite of 5 to 25% by volume fraction, and the balance mainly ferrite and bainite, in which the  $\underline{\text{ferrite}}$  average  $\underline{\text{grain}}$  size is 2 to 20  $\mu\text{m}$ , and the value obtained by dividing the retained austenite average grain size by the ferrite average grain size is 0.05 to 0.8, and also, the concentration of carbon in the retained austenite is 0.2 to 3%, and, in the method for producing the same steel sheet, steel having the above components is subjected to hot finish rolling so as to be finished at the Ar3 transformation point temperature to the Ar3 transformation point temperature +100°C, is thereafter retained in the temperature range of the Ar3 transformation point temperature to the Ar3 transformation point temperature for 1 to 20 sec, is subsequently cooled at a cooling rate of  $\geq 20$ °C/s and is coiled at a coiling temperature in the temperature range of >350 to <450°C.

COPYRIGHT: (C) 2002, JPO

Previous Doc Next Doc Go to Doc#

## **WEST Search History**

Hide Items Restore Clear Cancel

DATE: Thursday, October 11, 2007

<u>Set</u> Name	Query	<u>Hit</u> Count
DB=PGPB, USPT, USOC, EPAB, JPAB, DWPI; PLUR=YES; OP=OR		
L13	l6 and 420/8.ccls.	10
L12	l6 and 420/\$.ccls.	157
L11	16 and (burring or phosphate)	50
L10	L9 and (burring or phosphate)	14
L9	L6 and 148/320.ccls. and (ferrit\$2 adj grain)	147
L8	L6 and 148/320.ccls. and (ferrit\$2 adj grain)	147
L7	L6 and 148/320.ccls.	151
L6	steel and (c or carbon) and (mn or manganese) and (al or aluminum) and (ferrit\$2 near grain)	1157
DB=EPAB,JPAB,DWPI; PLUR=YES; OP=OR		
L5	11 same (burring or phosphate)	5
L4	12 same (burring or phosphate)	1
L3	steel same (c or carbon) same (mn or manganese) same (al or aluminum) same (ferrit\$2 adj grain) same (bainit\$2 or martensit\$2)	39
L2	steel same (c or carbon) same (mn or manganese) same (al or aluminum) same (ferrit\$2 adj grain)	285
L1	steel same (c or carbon) same (mn or manganese) same (al or aluminum) same ferrit\$2 same grain	891
	Name DB=P L13 L12 L11 L10 L9 L8 L7 L6 DB=E L5 L4 L3 L2	Name  DB=PGPB, USPT, USOC, EPAB, JPAB, DWPI; PLUR=YES; OP=OR  L13

END OF SEARCH HISTORY